



# *Link Management System (LMS)*

*Dynamic Network  
Management*

*Hardware Specifications*

*THE VALUE OF PERFORMANCE.*

***NORTHROP GRUMMAN***

# Link Management System (LMS)

## Dynamic Network Management

### Hardware Specifications

#### CPU

- Intel® i7 Quad Core 6th Gen Processor, 3.4 GHz

#### Storage & Memory

- 16 GB RAM
- Removable 1 TB SSD

#### Display

- Dual 24" 1920X1200 LCD (LED Backlit) Monitors

#### Multimedia

- Combo Drive (DVD-ROM/CD-RW)

#### Keyboard & Input

- USB Keyboard
- Two-button Optical USB Mouse with scroll wheel

#### Input/Output (I/O)

- Ethernet 10/100 x 6
- USB 3.0 x 4
- VGA x 2
- RS-232 x 2
- DVI-D
- Mini Display Port x 6
- USB 2.0 x 4

#### Software

- Microsoft Windows 10 Professional 64-bit
- Northrop Grumman's Link Management System

#### Dimensions & Weight

- Computer: 7"(H) x 19"(W) x 17.7"(D), 34 lbs.
- Monitor: 21.2"(H) x 21.9"(W) x 9.1"(D), 16.8 lbs.

#### Power Requirements

- Computer:
  - 90 - 264 VAC Auto Sensing, 47/63 Hz
  - 160 Watts (TYP), 800 Watts (MAX)
  - NEMA 5-15P Plug, Dual Input AC
- Monitor:
  - 100 - 240 VAC Auto Sensing. 50/60 Hz
  - 29 Watts (TYP), 55 Watts (MAX)
  - NEMA 5-15P Plug
- International Power Cords Available Upon Request

#### Transit Cases

- Rugged Computer Transit Case
- Rugged Monitor Transit Case
- ICY DOCK ToughArmor MB991SK-B 2.5" SATA HDD/SSD Full Metal Mobile Rack carrier for SSD

#### Standard Interfaces

- Link 16 (Host)
- MIDS Platform D/J
- Small Form Factor Terminals
- SADL(Gateway/ Generic Host)
- EPLRS
- JREAP (JREAP-C)
- SIMPLE/GCCS

#### Expansion

- Interface - Link 16 1553
  - Link 16 (Host/Monitor)
  - MIDS Platform A
  - Single or Dual Channel
  - MIDS JTRS
  - Navy Ship/Air
- Interface - Link 11 NTDS
  - Single Channel
  - Link 11 (Host)

#### For more information please contact:

Northrop Grumman  
Mission Systems  
9326 Spectrum Center Blvd.  
San Diego, CA 92123-1443

Product Sales:  
dataLink interop@ngc.com

Product Support:  
cis.productsupport@ngc.com