

THE VALUE OF PERFORMANCE.

***NORTHROP GRUMMAN***

## ***MARK VII***

*Handheld Eyesafe Laser Target Locator*

*Target Location During Day or Night Operations*

**T**he compact and lightweight Mark VII Eyesafe Laser Target Locator was developed for day/night use by artillery forward observers, forward air controllers and long range reconnaissance patrols.

The Mark VII incorporates advanced laser technology and a unique switchable day/night vision optical design, plus an embedded digital magnetic compass, to provide range, azimuth, and elevation digital data output for accurate target location determination.

With the Mark VII RS-232 output connected to a PLGR (Precision Light Weight GPS Receiver), accurate target coordinates are automatically computed for battlefield use.

In addition to serial data output in the PLGR protocol, output in the FED (Forward Entry Device) data format and a NMEA protocol are also available.

All three interface protocols are selectable in the Mark VII unit and growth has been provided for implementation of additional interface protocols.

The Mark VII laser resonator utilizes KTP OPO technology to produce the 1.57 $\mu$  output that is Class I eyesafe, making it usable under all operational and training conditions.

### **Features**

- Lightweight: 4.2 lbs. (1.9 kg)
- Ranges in Excess of 10 km
- Minimum Range of 20 meters
- Integrated Image Intensifier
- Day and Night Switchable
- Range, Azimuth and Elevation Provided for Target Location
- Class I Eyesafe Laser
- RS-232 Data Interface



## Technical Specifications

### General

- Size: 3.24 x 7.40 x 6.34 inches (8.2 x 18.8 x 16.1 centimeters)
- Weight: 4.2 lbs (1.91 kg) with battery
- Operating Temperature: -20° C (-4° F) to +50° C (+122° F)
- Storage Temperature: 30° C (-22° F) to +77° C (+170.6° F)

### Eyesafe Laser Transmitter

- Type: Nd:YAG with KTP OPO Converter
- Wavelength: 1.57 microns
- Pulse Rate: 6 per minute
- Minimum Range: 20 meters
- Maximum Range: 19,995 meters
- Range Increments: 3 meters
- Accuracy: +/- 3 meters
- Range Computation: Selectable First/Last

### Night Sighting Optics

- Type: Image Intensifier (Gen II, III or IV)
- Magnification: 4 x 50
- Field of View: 8.3 degrees (147 mils)
- Reticle: Projected, Open Center Crosshair with center dot
- Reticle: Projected, open center crosshair with laser aiming box

### Electronic Compass

- Type: Magnetoresistive
- Accuracy: 9 mil (2 sigma)

### Electronic Inclinometer

- Type: Gravity Sensor
- Accuracy: 4 mil (2 sigma)

### Day Sighting Optics

- Magnification: 7.3 x 18
- Field of View: 4.5 degrees (80 mils)
- Reticle: Projected, Open Center Crosshair with center dot

### Display

- Type: Projected in Eyepiece (Range, Azimuth, Elevation, Plus other Operational Data)

### Data Interface

- Type: RS-232 Port to Precision Lightweight
- Global Position System Receiver (PLGR), FED and NMEA

### Power

- Battery Type: Disposable 3.9V Lithium
- Vehicle Power
- Night Range Operations per Battery: > 1000

### For more information, please contact:

Northrop Grumman Corporation  
Electronic Systems  
Laser Systems  
2787 South Orange Blossom Trail  
Apopka, Florida 32703 USA  
Phone: (321) 354-3000  
24-Hour Customer Service:  
(800) 443-9219  
email: laser-systems@ngc.com

[www.northropgrumman.com](http://www.northropgrumman.com)

*Specifications and features subject to change without notice.*

© 2013 Northrop Grumman Systems Corporation  
All rights reserved.



DS-148-DAF-1001  
A330:  
ES-DSEA  
2013 RM Graphics

**THE VALUE OF PERFORMANCE.**

***NORTHROP GRUMMAN***